

RapidFire Retriever®



Features

- Retrieve hot parts off cutting tables with speed & precision!
- Increase production while reducing the potential for injury
- Powerful Rare Earth magnet hold parts securely
- “On-Command” release with just a quick blast of shop air
- Actuate release with just one finger, it’s as simple as the pull of a trigger



Lift - lbs (kg)	Ln. (in)	Wt. (lbs)	Model No.
35.0 (15.88)	24	2.1	RFR2400
35.0 (15.88)	36	2.3	RFR3600
35.0 (15.88)	48	2.5	RFR4800

Long Reach Retrievers



Ideal for reaching behind, underneath or around machinery and/or difficult to reach areas. All Ceramic tools have a maximum temperature of 300°F (148°C).



The MX3000WAH Lightweight long reach retriever has a round magnet at a 45 degree angle. The MM06X38 is a long retriever for narrow areas with a rectangular magnet.

Lift - lbs (kg)	Magnet Dimensions (in)	Ln. (in)	Wt. (lbs)	Model No.
A 47.5 (21.55)	3-1/4 Diameter	38	1.70	MX3000WAH
B 8.0 (3.63)	1-3/8 x 6	39.7	3.00	MM06X38

ON/OFF Magnetic Tie-Downs

Magnetic Tie-Downs, featuring Magswitch® technology, work extremely well for temporary or portable holding of tarps, signs, banners, etc. No need to drill, bolt or weld mounting tabs to steel surfaces. Just place the magnet on the clean steel, push the handle slightly down and rotate 180° and the magnet is “On”. Reverse steps to turn the magnet “Off”.

Features

- On/Off Permanent Rare Earth magnet
- Locking On/Off handle
- Performs best when mounted on a clean smooth, flat, metal surface that is at least 1/4” thick
- Works on Flat and Round ferrous surfaces
- 4:1 Design Factor
- MTD137MS has M6 tapped holes on all sides.



Hold - lbs (kg)	Ht. (in)	Wd. (in)	Ln. (in)	Wt. (lbs)	Model No.
30 (11.34)	3-1/2	1-1/2 Dia.	—	0.70	MTD030MS
60 (18.15)	4	2-3/4 Dia.	—	1.95	MTD060MS
137 (249.48)	5-3/4	2	3	3.75	MTD137MS

Parts Retrievers

Remove Steel Parts from bins, boxes, kegs, tables or floors.

Features

- Easy release of collected parts or scrap
- Powerful light-weight magnet
- Durable aluminum housing
- Comfortable non-slip handle



Handle	Lift - lbs (kg)	Ht. (in)	Wd. (in)	Ln. (in)	Wt. (lbs)	Model No.
Short	5.0 (2.27)	7-1/2	2-3/8	4-1/2	1.6	PR7100
Short	7.0 (3.18)	7-1/2	2-3/8	4-1/2	1.7	PR7200
Short	11.0 (4.99)	7-1/2	2-3/8	4-1/2	1.8	PR7400
Long	5.0 (2.27)	33-1/2	2-3/8	4-1/2	2.4	PR7100-30
Long	7.0 (3.18)	33-1/2	2-3/8	4-1/2	2.5	PR7200-30
Long	11.0 (4.99)	33-1/2	2-3/8	4-1/2	2.7	PR7400-30

ON/OFF Magnetic Utility Lifter

Stop bending over to lift and move steel pieces and scrap and reduce finger and toe injuries with this light-weight deep reach permanent magnetic lifter.

This Magnetic Utility Lifter, featuring Magswitch® technology, has a locking On/Off handle for safety. Rated up to 50 lbs.



Lift - lbs (kg)	Length (in)	Wt. (lbs)	Model No.
50.0 (22.68)	28.5	5.5	MCLVB01



Cutting Table Tools & Retrievers



Power Grips



Features

- Effective holding against shear force
- Securely grips heavy parts
- Maximum Temp. 300°F (148°C)



Lift - lbs (kg)	Ht. (in)	Wd. (in)	Ln. (in)	Poles	Wt. (lbs)	Model No.
25.0 (11.34)	2	3/4	2-1/8	2	0.40	AC2100WLH
51.5 (23.36)	2-1/4	3/4	4	2	0.75	AC2200WLH
92.5 (41.96)	2-3/4	1-7/8	5-1/4	4	2.40	AC2201WLH

ON/OFF Power Grips

Features

- Magswitch® Technology
- On/Off Rare Earth Design
- Securely grips heavy parts
- Works on flat or pipe
- Max. Temp. 180°F (82°C)



Lift - lbs (kg)	Ht. (in)	Wd. (in)	Magnet Dia. (in)	Wt. (lbs)	Model No.
55.0 (24.95)	3-3/4	4-1/4	1-1/2	0.75	ACS055MS
95.5 (43.09)	4-1/2	4-1/4	2-1/4	2.40	ACS095MS

Lift value on pipe varies based on diameter and wall thickness.

ON/OFF Cordless Power Grip

No more picking up sharp, hot or greasy steel with your hands. Experience fast pick-up and transport of small steel loads.

Features

- Push-Button, On/Off Controls
- Rare Earth permanent magnet will stay "On" if battery loses power
- Battery power "On" light, blinking light if battery needs recharging
- Includes charger and two batteries
- Up to 200 cycles per charge
- Works on flat or pipe
- Magswitch® Technology
- Max. Temp. 180°F (82°C)



Lift - lbs (kg)	Ht. (in)	Wd. (in)	Ln. (in)	Wt. (lbs)	Model No.
60 (27.22)	8-1/4	3	7	4.0	ACC060MS


Lift value on pipe varies based on diameter and wall thickness.

Magnetic Sheet Handlers

Features

- Lift or move sheets, plates, hot or oily parts
- Handle sheets stacked horizontally or vertically
- Protect workers from cuts, slivers, nicks & burns
- Increase productivity
- No electricity required

Note: Not intended to be used with a crane



Lift - lbs (kg)	Th. (in)	Wd. (in)	Overall Ln. (in)	Mag. Ln. (in)	Mag. Th. (in)	Wt. (lbs)	Max. Penetration (in)	Model No.
50.0 (22.6)	4	3-5/8	11-1/2	6-1/8	1-3/8	3.75	3/16	B100
125.0 (56.7)	4	7-1/4	11-1/2	6-1/8	1-3/8	8.25	5/16	B250
200.0 (90.7)	4	7-1/4	11-1/2	6-1/8	1-3/8	8.25	5/16	B400
300.0 (136.0)	4	7-1/4	11-1/2	6-1/8	1-3/8	8.25	5/16	B600



Low Profile Magnetic Retriever



Features

- Retrieve hot parts
- Reduce employee injury
- Keep hands out of press
- Handle is bendable to almost any angle or curve



Lift - lbs (kg)	Ht. (in)	Dia. (in)	Ln. (in)	Wt. (lbs)	Model No.
7.0 (0.91)	3/16	1-1/4	15	0.50	IMPL1000
19.0 (8.62)	5/16	2-1/32	15	0.63	IMPL2000

Grip Stick Retriever



Pick your lift Lbs., Magnet & Grip are interchangeable.

- Retrieve hot parts
- Keep hands out of press
- Reduce employee injury
- 10° angled handle



Lift - lbs (kg)	Magnet Type	Ht. (in)	Wd. (in)	Ln. (in)	Wt. (lbs)	Model No.
12.5 (5.67)	Ceramic	7/8	1-3/8	14	0.65	IMPL2100
43.5 (19.73)	Rare Earth	7/8	1-3/8	14	0.65	IMPL2104

Magnetic TriggerLift®



Hand held lift grips parts with an easy to use trigger release.

Features

- Retrieve hot parts from cutting tables
- One handed operation
- Permanent magnet
- Move parts faster and easier
- Aluminum housing
- Maximum Temp. 300°F (148°C)



Lift - lbs (kg)	Ht. (in)	Wd. (in)	Ln. (in)	Wt. (lbs)	Model No.
50.0 (22.68)	4-13/16	2-3/8	3-3/8	1.50	B090