

# Wire rope lever hoists

## Engineered for Reliable Operation

- Handle Designed for Overload Protection—Handle bends to warn of hazardous condition and prevent dangerous overload.
- Hooks with Hook Latches—360° swiveling hooks equipped with latches for positive load engagement.
- Meets ANSI Standard B30.21.
- Tested to 125% of Capacity.
- Made in U.S.A.

## Portable and Durable

- Lightweight and Rugged—Special cast aluminum alloy housings.
- Heavy Duty Cable—Utilizes preformed and galvanized 7 x 19 (133 strand) extra flexible aircraft cable.
- Corrosion Resistant—All stainless steel springs and shafts.
- Reduced Wear—All rotating shafts are mounted on bronze bushings.

## Easy to Operate

- Self-storing Cable Drum—Provides compact operation.
- Fast Cable Take-up—Winding wheel provided for quick take-up or positioning of cable.
- Easy Load Positioning—Utilizes a double interlocking pawl system for precise load adjustment.
- Positive Load Holding in All Environments—Provided by double interlocking pawl mechanism.
- Open Construction—Allows for easy cleaning and inspection.

## Special Model Features

- All models are available with Bullard-type hooks.
- CM430CDPA equipped with oversized slip hooks— ideal for opening and closing boxcar doors.



<b>* ⚠ WARNING</b>
Overloading and improper use can result in injury.
<b>To avoid injury:</b> <ul style="list-style-type: none"> <li>• Do not exceed working load limit, load rating capacity</li> <li>• Do not use to lift people or loads over people.</li> <li>• use only alloy chain for overhead lifting.</li> <li>• Read and follow all instructions.</li> </ul>

**McLaughlin Hoist & Crane  
Authorized Sales & Service**

**(636) 343-9700**

**[www.stlcrane.com](http://www.stlcrane.com)**

Single & Double Line • 1000 - 4000 Lbs.

Specifications		SINGLE LINE			DOUBLE LINE			Cable Dia. x Length (In.) (Ft.)	Ship Weight (Lbs.)
		Capacity (Lbs.)	Lift (Ft.)	Hook to Hook (Min.) (In.)	Capacity (Lbs.)	Lift (Ft.)	Hook to Hook (Min.) (in.)		
Product Code	Model								
04601W	115SA	1000	13¾	19	—	—	—	¾/16 x 16	8¾
04602W	115DA	1000	13½	21	2000	6 ½	27	¾/16 x 16	10½
04610W	505NA	1500	13	21	—	—	—	¼ x 15	9½
04611W	202WNA	1500	12½	21	3000	6	27	¼ x 15	11½
04620W	434WNA	1500	21½	22½	3000	10¼	28½	¼ x 24	13¼
04621W	430CDPA	1500	21½	25	3000	10¼	33½	¼ x 24	16
04631W	404WNA	2000	12½	22½	4000	6	28½	9/32 x 15	13½